Practitioner's Docket No. U 013869-1

PATENT

TRANSMITTAL LETTER TO THE U.S. DESIGNATED OFFICE (DO/US)--ENTRY INTO THE U.S. NATIONAL STAGE UNDER CHAPTER I

INTERNATIONAL APPLICATION NO. PCT/CN01/00973		INTERNATIONAL FILING DATE 15 JUNE 2001		G DATE PRIORITY DATE CLAIMED 15 JUNE 2000
TITLE OF INVENTION				
FULLY VULCANIZED THERMOPLASTIC POWDERY SILICONE RUBBER,				
PREPARATION AND USE THEREOF				
APPLICANT(S)				•
1.	XIAOHONG ZHAN	G	6.	SHIJUN ZHANG
2.	JINLIANG QIAO		7.	ZHIHAI SONG
3.	GENSHUAN WEI	•	8.	JIUQIANG LI
4.	JIANMING GAO		9.	YICAI ZHU
5.	YIQUN LIU			

Box PCT **Assistant Commissioner for Patents** Washington D.C. 20231

ATTENTION: DO/US

Optional Customer No. Bar Code



PATENT TRADEMARK OFFICE

PRELIMINARY AMENDMENT

Please amend the above identified application as follows:

3. (Amended) The fully vulcanized powdery silicone rubber according to claim 1, characterized in that the fully vulcanized powdery silicone rubber has a gel content of at least 60% by weight, preferably at least 75% by weight.

CERTIFICATION UNDER 37 C.F.R. 1.10*

(Express Mail label number is mandatory.) (Express Mail certification is optional.)

I hereby certify that this paper, along with any document referred to, is being deposited with the United States Postal Service on this date FEBRUARY 11, 2002 in an envelope as Express Mail Post Office to Addressee," mailing Label Number EV 011020553 US, addressed to the: Assistant Commissioner for Patents, Washington, D.C. 20231.

name of person mailing paper)

Signature of person mailing paper

WARNING:

Certificate of mailing (first class) or facsimile transmission procedures of 37 C.F.R 1.8 cannot be used to obtain a date of mailing or transmission for this correspondence.

*WARNING:

Each paper or fee filed by "Express Mail" must have the number of the "Express Mail" mailing label placed thereon prior to mailing. 37 C.F.R 1.10(b).

"Since the filing of correspondence under § 1.10 without the Express Mail mailing label thereon is an oversight that can be avoided by the exercise of reasonable care, requests for waiver of this requirement will not be granted on petition." Notice of Oct. 24, 1996, 60 Fed. Reg. 56,439, at 56,442. EXPRESS MAIL LABEL

NO.: EV 011020553 US

- 4. (Amended) The fully vulcanized powdery silicone rubber according to claim 1, characterized in that the fully vulcanized powdery silicone rubber particle has a homogeneous structure.
- 5. (Amended) A process for preparing the fully vulcanized powdery silicone rubber, which comprises vulcanizing a corresponding feed silicone rubber by means of irradiation.
- 6. (Amended) The process according to claim 5, characterized in that latex of organosilicon polymer of copolymer having lower molecular weight is used as the feed silicone rubber and irradiated with a high-energy source in the presence or absence of a crosslinking agent, and the fully vulcanized powdery rubber is obtained by drying after the irradiation.
- 10. (Amended) The process according to claim 6, characterized in that a crosslinking agent is added during the irradiation, and is selected from monofunctional, difunctional, trifunctional, tetrafunctional and multifunctional crosslinking agent, and any combination thereof.
- 12. (Amended) The process according to claim 10, characterized in that the amount of the crosslinking agent added is 0.1 to 10% by weight, preferably 0.5-7% by weight, more preferably 0.7-5% by weight, based on the solid content of latex of organosilicon polymer or copolymer having lower molecular weight.
 - 13. (Amended) The process according to claim 6, characterized in that drying is

carried out by spray drying with a spray dryer or by precipitation drying method, preferably spray drying.

Respectfully submitted,

WILLIAM R. EVANS

LADAS & PARRY 26 WEST 61ST STREET

NEW YORK, NEW YORK 10023 REG.NO.25858(212)708-1930

MARKED-UP COPY

- 3. (Amended) The fully vulcanized powdery silicone rubber according to claim 1 [or 2], characterized in that the fully vulcanized powdery silicone rubber has a gel content of at least 60% by weight, preferably at least 75% by weight.
- 4. (Amended) The fully vulcanized powdery silicone rubber according to [any one of] claim[s] 1 [to 3], characterized in that the fully vulcanized powdery silicone rubber particle has a homogeneous structure.
- 5. (Amended) A process for preparing the fully vulcanized powdery silicone rubber, which comprises vulcanizing a corresponding feed [latex of organosilicon polymer or copolymer] silicone rubber by means of irradiation.
- 6. (Amended) The process according to claim 5, characterized in that latex of organosilicon polymer of copolymer having lower molecular weight is used as the feed [latex] silicone rubber and irradiated with a high-energy source in the presence or absence of a crosslinking agent, and the fully vulcanized powdery rubber is obtained by drying after the irradiation.
- 10. (Amended) The process according to [any one of] claim[s] [to 9], characterized in that a crosslinking agent is added during the irradiation, and is selected from monofunctional, difunctional, trifunctional, tetrafunctional and multifunctional crosslinking agent, and any combination thereof.

- 12. (Amended) The process according to claim 10 [or 11], characterized in that the amount of the crosslinking agent added is 0.1 to 10% by weight, preferably 0.5-7% by weight, more preferably 0.7-5% by weight, based on the solid content of latex of organosilicon polymer or copolymer having lower molecular weight.
- 13. (Amended) The process according to [any one of] claim[s] 6 [to 12], characterized in that drying is carried out by spray drying with a spray dryer or by precipitation drying method, preferably spray drying.